

SVB1™

Are you in search of a small, lightweight, high-impact lighting fixture that gives you an edge over the competition? Look no further! Introducing the eye-catching SVB1™ effect, beam, and wash luminaire!



Light source

1 module - containing 7 x 40W RGBW multichips, middle pixel containing additional 200W white strobe LEDs



Light output

11.000 lm, 17.500 lx



Zoom range

3,8° - 50°



Effects

Pixel control, Motorised exceptionally quiet zoom, Electronic strobe effect, Virtual colour wheel, Tungsten lamp effect, Preprogrammed pixel effects, Continuous pan and tilt movement, ScreenPix, White strobe effects



This versatile, compact powerhouse, built on the heritage of its SVOPATT™ lineage, delivers high- output and extreme speed with continuous pan and tilt rotation, ensuring a captivating performance for your audience.

Equipped with seven individual 40W RGBW LED cells and a central pixel featuring both RGBW and a powerful 200W white strobe LED module, the SVB1™ offers full pixel mapping capabilities for unlimited creative looks and effects, boasting an impressive 11.000 lm output.

Helping to maintain this high level of performance, the RLCT™ lens coating protects against scratches and scuffs while preventing particle adhesion, ensuring your optics stay cleaner for far longer.

The SVB1™ stands out with its motorized zoom range, offering precise 3.8° beams to expansive 50° washes, all while operating with remarkable quietness. Its rapid speed and wide coverage are further enhanced by the fixture's 360° continuous pan and rotation capabilities, making it an impressive choice for any lighting setup.

With a choice of RGB or CMY colour mixing modes, a variable CCT range from 1,700K to 20,000K, an onboard DataSwatch™ colour library with 66 preset colours, and tungsten lamp emulation, the SVB1™ provides a comprehensive colour control set.

Designed for noise-sensitive environments, the SVB1™ operates at an ultra-quiet 18 dB(A) in quiet mode due to its advanced cooling technology and noise dampening design. Along with Cpulse™ software for on-screen flicker removal and +/- green content control, this luminaire is ideal for studio environments.

A multitude of modes and protocols, including ArtNet and sACN, ensures easy pixel mapping. Network communication is streamlined with REAP™ (Robe Ethernet Access Portal), while the Epass™ Ethernet pass-through switch maintains connectivity even when the fixture is powered off.

Weighing just 7.2 kg, the compact and feature-packed SVB1™ offers exceptional speed, accuracy and punch, making it the perfect enhancement for any performance!

SVB1™ - Enhancing your impact!

Technical Specification

Source

- Light source type:
 - 1 module - containing 7 x 40W RGBW multichips
 - middle pixel containing additional white strobe LEDs
- LED life expectancy: min. 50.000 hours
- Typical lumen maintenance: L70/B50 @ 50.000 hours

Optical system

- Robe's proprietary optical design
- High-efficiency zoom optical system, ratio 13:1
- Zoom range: 3.8° - 50°
- Diffusion filter imbedded
- Fixture total lumen output:
 - 11.000 lm (integrating sphere)
 - 8.600 lm (goniophotometer)
- Illuminance: 17.500 lx @ 5 m
- RLCT™ Innovative lens coating technology

Dynamic Effects and Features

- Colour mixing mode RGBW or CMY
- + - Green correction function
- Individually controllable Strobe LED zone
- White light: Variable CCT 1.700K - 20.000K
- DataSwatch™ filters: pre-programmed 66 colours and tones including most used whites 2.700K, 3.200K, 4.200K, 5.600K and 8.000K
- Tungsten lamp effect: 750W, 1.000W, 1.200W, 2.000W, 2.500W lamp emulation for whites from 2.700K to 4200K (red shift and thermal delay)
- Motorised exceptionally quiet zoom
- High resolution electronic dimming: 0 - 100%
- Electronic strobe effect with variable speed up to 20 Hz, pre-programmed random strobe & pulse effects
- L3™ - (Low Light Linearity) Imperceptible 18 bit dimming for ultra smooth fade to black
- Cpulse™ special flicker-free management for HD and UHD cameras, ready for 8K and 16K

Control and programming

- Setting & Addressing: ROBE Navigation System 3 (RNS3)
- Display: QVGA Robe touch screen with battery backup, gravitation sensor for auto screen positioning, operation memory service log with RTC, stand-alone operation with 3 editable programs (each up to 100 steps), built-in analyser for easy fault finding, NFC app controller
- Protocols: USITT DMX-512, RDM, ArtNet, MA Net, MA Net2, sACN
- REAP™ - Robe Ethernet Access Portal
- Wireless CRMX™ technology from Lumen Radio - On request
- Epass™: Ethernet pass through switch which sustains Ethernet integrity, when the fixture has no power, to automatically maintain network connectivity - On request
- DMX Protocol modes: 3
- Control channels: 28, 61, 58
- RGBW / CMY: 8 or 16 bit
- Pan & Tilt resolution: 8 or 16 bit
- Zoom: 8 or 16 bit
- Dimmer: 8 or 16 bit (internal 18 bit)

Movement

- Automatic Pan & Tilt position correction
- Pan movement range 540° with continuous rotation control
- Movement control: Standard and Speed
- Tilt movement range 360° with continuous rotation control
- Controllable speed of Pan & Tilt movement

Thermal specification

- Maximum ambient temperature: 45°C (113°F)
- Maximum surface temperature: 70°C (158°F)
- Minimum operating temperature: -5°C (23°F)

Noise Levels

- Sound pressure level:
 - 18 dB(A) at 1 m (quiet mode)
 - 34 dB(A) at 1 m (auto mode)
- Sound power level:
 - 26 dB(A) (quiet mode)
 - 42 dB(A) (auto mode)

Electrical specification and connections

- Power supply: Electronic auto-ranging
- Input voltage range: 100-240 V, 50/60 Hz
- Power consumption: Max. 330 W
- Power connector in/out: Neutrik powerCON TRUE1
- DMX and RDM data in/out: Locking 5-pin XLR connectors
- Ethernet port in/out: RJ45, for Embedded Epass™ switch 10/100 Mbps - On request

Approvals

- CE Compliant
- cETLus Compliant

Mechanical specification

- Height: 398 mm (15.7") - head in vertical position
- Width: 281 mm (11")
- Depth: 186 mm (7.3") - head in vertical position
- Weight: 7.2 kg (15,87 lb)
- Ingress protection rating: IP20

Rigging

- Universal operating position
- Safety cable attachment point

Included items

- User Manual
- Omega Adaptor CL-regular

Optional accessories

- Doughty Trigger Clamp: 17030386
- Safety wire 36 kg: 99011963
- Wireless DMX external module: 10980127
- Mains Cable powerCON TRUE1 In/Schuko, 2m, Indoor: 13052405
- Mains Cable powerCON TRUE1 In/US, 2m, Indoor: 13052406
- Mains Cable powerCON TRUE1 In/CEE 16A, 2m, Indoor: 13052445
- Mains Cable powerCON TRUE1 In/Open ended, 2m, Indoor: 13052407
- Daisy Chain powerCON TRUE1 In/Out, EU, 2m, Indoor: 13052439
- Daisy Chain powerCON TRUE1 In/Out, US, 2m, Indoor: 13052440
- Daisy Chain powerCON TRUE1 In/Out, EU, 5m, Indoor: 13052444
- Single Top Loader Case: 10120361
- Quad Top Loader Case: 10120362
- Eight Pack Top Loader Case: 10120363
- Foam Shell: 20020505

Legal

- SVB1™ is a Trademark of Robe lighting s. r. o.
- SVB1™ is patented by Robe lighting s. r. o. and is protected by one or more pending or issued patents